



8600 Series Bar Code Scanner & Imager

- 2D imager ring with 21" scan distance.
- Enhanced white LED flash illumination.
- SR laser ring with 45" scan distance.
- Either available with long cables to attach to hip-flip or voice case.

Scan Rate

8600 SRS
Imager Series

Depth of Field

8600 SRS
Imager
Min. 3.5"
Max. 21"

IP Rating

8600 SRS Imager
IP54

Temp Range

8600 SRS Imager
-4° to 122° F

Symbologies Supported

8600 SRS Imager & Laser Scanner -1D
Chinese 2 of 5, Codabar, Code 11,
Code 128, Code 39, Code 93,
Discrete 2 of 5, Interleaved 2 of 5,
MSI Plessey, RSS, UPC/EAN:
UPC-A, UPC-E, UPC-E1, EAN-8,
EAN-13

8600 SRS
Laser Series
36/ sec.

8600 SRS
Laser Scanner
Min. 1"
Max. 45"

8600 SRS Laser
Scanner
IP54

8600 SRS Laser
-4° to 122° F

8600 SRS Imager - 2D
PDF417, MicroPDF, Code 128 Emul,
Data Matrix, Maxicode, QR Code,
Postal Codes

*RoHS compliant versions available for all LXE scanners



ORACLE PARTNER



125 Technology Parkway Norcross, GA 30092 1-800-664-4593 www.lxe.com