

Zebra® RZ™ series printers



RFID industrial/commercial printer/encoders

The RZ400™ and RZ600™ printer/encoders bring UHF RFID capabilities to Zebra's popular Z Series® platform and set the new standard as the price-performance leaders in meeting the needs of today's global RFID-tagging compliance initiatives. These metal printer/encoders offer EPC Gen 2 support, high-speed print throughput and rugged reliability to enhance productivity in tough environments and lower duty-cycle applications.

Better connected for a connected world

The RZ series RFID printer/encoders connect easily with most warehouse/manufacturing and business applications. The RZ400 and RZ600 are better connected to your network – through USB 2.0, 802.11b/g secure wireless or Ethernet.

They're better connected to your applications – with multiple RFID power settings to adjust to current and future RFID protocols, transponder designs and sizes; choice of print resolution including 300dpi and XML-enabled printing as a standard feature.

Also they're better connected to your needs – with easy setup via a large easy-to-read front panel that includes Asian-language support; easy loading of supplies and easy maintenance with quick-changing printheads and platens.



Key features

- Optimised RFID for fastest label throughput
- Variable RFID power settings for flexibility
- Secure 802.11b/g wireless

Ideal for

- Case- and pallet-level identification
- Asset-tracking and inventory management
- Work in progress
- Shipping/receiving
- Distribution

Specifications at a glance*

Standard features

- Integrated UHF reader/encoder
- EPC Gen 2/ISO 18000-6C
- Full range of RFID power settings
- RFID processes optimised for fastest label throughput
- RFID counters keep track of the good and unusable labels
- Variable RFID power settings for both read and write allow maximum flexibility for printing small labels
- 32-bit 133MHz RISC processor
- Zebra printer driver for Windows® 3.x and 95/98/Windows NT®/2000/XP/2003 operating systems
- Advanced label/media counters
- Print methods: thermal transfer or direct thermal
- Construction: die-cast aluminium base, frame and printhead mechanism
- Metal media cover with large clear window
- Element Energy Equalizer™ (E3™) for superior print quality
- Auto-calibration
- Real-time clock
- Auto-ranging (90–265VAC) power supply
- Colour-coded operator cues
- Multi-language control panel with backlit 240x128-pixel display
- ZPL II®
- XML-enabled printing – direct-connect integration for bar code label printing that eliminates licence fees and print-server hardware and lowers customisation and programming costs

Printer specifications

Resolution

- 8 dots per mm/203dpi; 12 dots per mm/300dpi

Memory

- Standard: 8MB flash, 16MB DRAM
- Optional: factory-installed 64MB flash

Print width

- RZ400: 104mm/4.09"
- RZ600: 168mm/6.6"

Print length

- RZ400: with 203dpi: 3,988mm/157"; with 300dpi: 1,854mm/73"
- RZ600: with 203dpi: 2,590mm/102"; with 300dpi: 1,143mm/45"

Print speed

- 203dpi: 254mm/10" per second
- 300dpi: 203mm/8" per second

Media sensors

- Fixed reflective sensor
- Adjustable transmissive sensor

Media characteristics

Maximum label and liner length

- Maximum non-continuous: 991mm/39"

Maximum label and liner width

- RZ400: 114mm/4.5"
- RZ600: 178mm/7.0"

Maximum roll diameter

- 203mm/8.0"

Core diameter

- 76mm/3"

Media thickness

- 0.058mm/0.0023" to 0.25mm/0.010"

Media types

- Continuous, die-cut, tags, black-mark

Ribbon characteristics

Outside diameter

- 81.3mm/3.2"

Standard length

- 300m/984' or 450m/1,476'

Ratio

- 3:1 media roll to ribbon. Ribbon must be at least as wide as media

Width

- RZ400: 51mm/2.00" to 110mm/4.33"
- RZ600: 51mm/2.00" to 174mm/6.85"

Ribbon setup

- Ribbon wound ink-side out (ribbon wound ink-side in can be used with optional ribbon spindle on RZ400)

Core I.D.

- 25.4mm/1.0"

Operating characteristics

Environmental

Operating temperature:

- 0°C to 40°C/32°F to 104°F (direct thermal)
- 5°C to 40°C/40°F to 104°F (thermal transfer)

Storage temperature:

- -40°C to 60°C/-40°F to 140°F

Operating humidity:

- 20–85% non-condensing

Storage humidity:

- 5–85% non-condensing

Electrical

- Universal auto-ranging (PFC-compliant) power supply 90–265 VAC; 48–62Hz

Agency approvals

- FCC subpart B & C, IC RSS 210, IEC 60950-1, EN 300 220, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3
- Markings: cTUVus, CE, FCC-B, ICES-003, C-Tick

Physical characteristics

Width

- 278mm/10.9"

Height

- 338mm/13.3"

Depth

- 475mm/18.7"

Weight

- 15kg/32.4lb

Shipping weight

- 22kg/49lb

ZebraLink™ Solutions

Software

- ZebraDesigner™ Pro
- ZebraDesigner for XML
- ZebraDesigner label design software
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v7.0
- Zebra Universal Driver
- ZBI-Developer™
- Additional scalable and bitmapped fonts available

Networking/Connectivity

- ZebraNet® Internal Wireless Plus
- ZebraNet 10/100 Print Server
- RS-232C serial port
- High-speed IEEE 1284 bi-directional parallel interface
- USB 2.0

Firmware

- ZPL II
- XML-enabled printing
- Web View
- Alert
- ZBI 2.0™

Fonts/graphics/symbologies

Fonts and character sets

- Seven bitmapped, one smooth-scalable
- Native OpenType® font support
- Global printing – Unicode™-compliant
- Contains UFST® from Monotype Imaging Inc.

Graphic features

- Supports user-defined fonts and graphics, including custom logos
- ZPL II drawing commands for boxes and lines

Bar code symbologies

- Linear bar codes: Codabar, Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case C Codes, EAN-8, EAN-13, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Planet Code, Plessey, Postnet, Standard 2-of-5, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions
- Two-dimensional: Aztec Code, Codablock, Code 16K, Code 49, Data Matrix, GS1 DataBar (RSS), MaxiCode, MicroPDF417, PDF417, QR Code, TLC 39

Options and accessories

- Factory-installed 64MB flash memory option
- Cutter with catch tray
- Peel – a front-mount passive-peel option with no liner take-up
- Liner take-up (works with peel option) – full roll liner take-up spindle (fits standard base, RZ400 only)
- Rewind – internally rewinds full label roll on 76mm/3" core (comes with taller, non-standard printer base)
- RS-422/RS-485 serial port adaptor

*Specifications subject to change without notice.

©2008 ZIH Corp. E3, Element Energy Equalizer, ZBI 2.0, ZBI-Developer, ZebraDesigner, ZebraLink, ZebraNet and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head, Z Series, ZebraNet and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Unicode is a trademark of Unicode, Inc. UFST is a trademark of Monotype Imaging Inc. and may be registered in certain jurisdictions. OpenType, Windows and Windows NT are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. For optimal printing quality and proper printer performance across our product line, Zebra strongly recommends the use of genuine Zebra supplies as part of the total solution. Specifically, the RZ400 and RZ600 are designed to work only with genuine Zebra printheads, thus maximising safety and print quality.



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 Fax: +44 (0)1628 556001 E-mail: mseurope@zebra.com Web: www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East, Africa & India: Dubai, India, South Africa